

# 9002, 9050BF

## 19 Rack-mount chassis with power supply

### DESCRIPTION

The Model 9002 19" 4 RU chassis is designed for rack mounting Optelecom® Series 9000 cards. All electrical and optical connections are made to the front panels of the plug-in cards.

Individual cards can be hot swapped without affecting the operation of other cards in the chassis. The rack mounting ears may be installed on the front or rear of the chassis as required for the specific application.

The 9002 may be equipped with one or two power supplies (9050BF). You can set these supplies to operate as load-sharing or as primary and backup supplies. 18 slots are available for use with one supply installed; 15 are available with two supplies installed. The chassis supports the Network Management System.

### FEATURES

---

Rack-mountable chassis supports 9000 series rack-mount cards

---

Supports up to 21 slots

---

3-slot, heavy duty, fan-cooled power supply module

---

Output voltage, current, and temperature monitoring

---



### 9050BF rack-mount power supply

These 6.0VDC power supplies are intended to meet the requirements of Series 9000 chassis rack mount units. The supplies may be operated as a single supply or, when two supplies are installed, primary/backup mode or load-sharing mode. Adjustments are made simple by a set of front panel meter test points for output voltage, current, and temperature and a voltage adjustment control. For noise immunity and proper ventilation, install blank panels over unused slots. See the accessories chart in Ordering Information below. Power supplies are ordered separately; the version of supply required depends on the number of cards installed and their total power consumption. Refer to the User Manual and system applications notes available from the factory for details on installing the 9002 chassis.

#### Mechanical

Number of slots	21
Type of slot	9000 series
Dimensions (h x w x d)	19"/4RU: 177.8 x 442.6 x 203.2 mm (7" x 19" x 8")
Weight	2.72 kg (6 lbs)

#### Power supply (9050BF)

Input voltage rang	100-240VAC, 50/60Hz
Output voltage	6.1 Vdc
Maximum current	24A at -40°C to +50°C (-40°F to +122°F)
Maximum current derated	13.5A at -40°C to +65°C (-40°F to +149°F)
Number of fans	1
Number of slots used	3
Dimensions (h x w x d)	154.9 x 60.9 x 218.4 mm (6.1" x 2.4" x 8.6")
Weight	1.45kg (3.2lbs)

#### Environmental

Operating temperature	-40°C to +74°C (-40°F to +165°F)
Storage temperature	-55°C to +85°C (-67°F to +185°F)
Relative humidity	<95% with no condensation

#### Ordering information

9002	21-slot 19" rack-mount chassis (without power supply unit, 9050BF)
9050BF	3-slot power supply unit for use with the 9002 chassis
9996	1 single blank panel (1-slot cover plate)
9998	1 triple blank panel (3-slot cover plate)

