CKKK-SERIES

Hingeable Security Camera poles

DESCRIPTION

The CKKK reversible camera pole are suitable for every type of camera system. This CKKK camera poles are hingeable and available in three different lenghts, complete with anti climb, connection terminal and concrete plates for direct burial. The standard poles are galvanized, however by providing the RAL color customization is possible.

FEATURES

- Available in 4, 6 and 8 meters
- RAL Color customization possible
- Two concrete stabilization plates and a stock cap included
- Detachable anti-climb Security
- Hingeable



Optional expansions:

- Camera adapter with tilt mechanism (45°)

Mechanical	
Attachments	No, only stock cap
Climbing prohibition	Yes, removable
Tilt over	Yes
Stabilisation plate	Yes, 2 prefab concrete plates with mounting brackets for direct burial
230V connector	Terminal block with clamps
RAL colour	Optional
Optional	Base plate, anti-vandalism closure, doorlock A-V closure

CKKK4	
length above ground level	4.0 m
length below ground level	800 mm
Inspection door	300 x 80 mm
Weight	67 kg

CKKK6	
Length above ground level	6.0 m
Length below ground level	1.200 mm
Inspection door	300 x 80 mm
Weight	101 kg

CKKK8	
Length above ground level	8.0 m
Length below ground level	1.250 mm
Inspection door	300 x 80 mm
Weight	138 kg

Ordering Info	
CKKK4	4m hinged camera pole+anti-climb
CKKK6	6m hinged camera pole, anti-climb
CKKK8	8m hinged camera pole, anti-climb
CKKK6-RAL	6m hinged camera pole, anti-climb, RAL-xxxx
CKKK4-RAL	4m hinged camera pole, anti-climb, RAL-xxxx
CKKK8-RAL	8m hinged camera pole, anti-climb, RAL-xxxx

Option	
DKO	Single camera adapter with tilt mechanism (45°)





