

CVKK-SERIES

Cylindrical Hinged Camera Poles

DESCRIPTION

The CVKK cylindrical camera pole are suitable for every type of camera system. This CVKK camera poles are cylindrical shaped, hingeable and available in three different lengths, complete with anti climb, connection terminal and concrete plates for direct burial. The standard poles are galvanized, however by providing the RAL color customization is possible.

FEATURES

Available in 4 and 6 meters

RAL Color customization possible

Two concrete stabilization plates and a stock cap included

Detachable anti-climb Security

Hingeable

Cylindrical shaped



Required expansion:

- Kaalfix key

Optional expansions:

- Camera adapter with tilt mechanism (45°)

Mechanical	
Attachments	No, only stock cap
Climbing prohibition	Yes, removable
Tilt over	Yes
Stabilisation plate	Yes, 2 prefab concrete plates with mounting brackets for direct burial
230V connector	Terminal block with clamps
RAL colour	Optional
Optional	Base plate, anti-vandalism closure, doorlock A-V closure

CVKK4	
length above ground level	4.0 m
length below ground level	1000 mm
Inspection door	400 x 85 mm
Weight	71 kg

CVKK6	
Length above ground level	6.0 m
Length below ground level	1200 mm
Inspection door	400 x 85 mm
Weight	101 kg

Ordering Info	
CVKK4	4m cylindrical reversible camera pole, anti-climb
CVKK6	6m cylindrical reversible camera pole, anti-climb
CVKK6-RAL	6m cylindrical reversible camera pole, anti-climb, RAL-xxxx
CVKK4-RAL	4m cylindrical reversible camera pole, anti-climb, RAL-xxxx
CVKK-KEY	Kaafix Key required for each site with CVKK poles

Option	
DKO	Single camera adapter with tilt mechanism (45°)





KAALFIX KEY (REQUIRED)



