

# IPH-S24

## iProtect Server S24

### DESCRIPTION

TKH Security has chosen an OEM platform with robust and powerful features. The servers are compiled based on requirements of the specific iProtect system: The iProtect Server S24 server can be used for all iProtect Access configurations. In addition, it is suitable for application of small to medium-sized iProtect Security configurations.



**Model IPH-S24****System**

Operating system	Ubuntu
Hard disk OS	500GB SSD in RAID01 (included)
Raid configuration	Non (see NVH-1004XR for RAID config)
Processor	Intel Xeon E2200 processor
Chipset	Intel C242 Chipset
Memory	16GB memory
Network Interface	4 x 1GbE LAN + 1 x Mgmt LAN (operable in combination with NVH-RMMv2) LAN controller supports 100Base-T, 1000Base-T
Video output	VGA
Drive bay	4 x 3.5" Hot-swap

**Mechanical**

Form Factor	1U 19-inch rackmount
Dimensions (DxWxH)	547.6 x 438.5 x 43.5 (mm)

**Electrical**

Power Input	100-240VAC, 50/60Hz 5A
Power Supply	400W Single
Power Consumption	200W

**Environmental**

Operating Temperature	5° C - 40° C (41°F - 104°F)
Storage Temperature	-40° C - 65° C (-40°F - 149°F)

**Ordering Info**

NVH-1004X	Video server 19", 1U, 4 bay HS, Xeon, SSD
Supplied Accessories	USB Compact Keyboard
	USB Optical Mouse
	Power Cord 1.5 meter
	Slide rail





RELATED

---

**iProtect**  
ACCESS


**iProtect iProtect Access**  
IPS-ACC

---

**iProtect**  
SECURITY


**iProtect iProtect Security**  
IPS-SEC

---



**iProtect 502-3045/E**  
KP 44 Server

---



**iProtect IPH-S10**  
iProtect Server IPH-S10

---