

JUNO

JUNO

IoT Controller

DESCRIPTION

Street cabinets without power or connectivity. Until recently, there was no control of these locations in the day-to-day management of these technical areas. With the advent of the TKH Security JUNO controller, the status of a passive location is always known.

FEATURES

- Managing unmanned locations in critical environments
- Determine the status at any given point
- Combines access management and monitoring
- Especially for street cabinets without power or connectivity



JUNO smart controller with IoT technology

Juno combines access management and monitoring of environment variables. It enables operations managers of critical infrastructures to check the status of their locations remotely. JUNO measures the temperature and humidity in the street cabinet, checks whether the cabinet still stands in an upright position, and it also monitors water on the floor and the position of the door. So you're always totally in control!

JUNO is a powerful, future proof solution that offers site managers complete control

Managing unmanned locations in critical environments, such as telecom and utility services, is increasingly subject to European regulations. It must be possible to determine the status of these locations at any given point in time. The control and granting of access must take place automatically and remotely from an efficiency point of view.

Housing

Dimension(LxBxH) 190x135x44 mm

Weight (no battery)

IP-rate IP54

Materia ABS Terluran GP22

External power supply

Voltag 513,6VDC

Current 1A

Battery

Technology Lithium-Thionyl Chloride

Power 3,6V

Bluetooth

Supports Version 5.0

Band 2,4 GHz ISM 2402 ~ 2484

LPWAN

Technology LoRaWAN

NB-IoT *

LTE-M *

Card socket

Type Micro-SIM *

Antenne

Type SMA plug 824 ~ 960 / 1,920 ~ 2,170 GHz *

433MHz /868MHz /915MHz

Onboard sensor

Temperature/ Humidity sensor Fully calibrated, linearized, and temperature compensated

Range: -40°C to 90°C and 10% to 90% Accuracy tolerance: 2%RH and 0.3°C

Tilt detection Tilt X, Y, Z

Lock connection

Connector type RJ45 Unshielded

Digital input 3

Lock output 3,6V Max. 100 mA

Indicator (LED) 3,6V

Input-Output Specifications

Specs



Input-Output Specifications

1	PC power	External DC power connection 5 - 13,6V DC
2	Electronic lock	EMKA low power lock (art.nr.1317-U00155-00000BO)
3	Antenna	LTE NB-IOT
4	Antenna	LoRa
5	not defined	ADC
6	Water leak sensor	External input analog
7	not defined	Eternal output
8	Door contact	External input digital normally open











RELATED



iProtect 571-0500
iProtect Site Software



Apollo ASM-AP-X
ApolloN



Apollo 570-0001
Apollo controller 230V