

# LCD-VMS NAV

## VMS-NAV 1x2

### DESCRIPTION

The Park Assist LCD-NAV 55 is a highly customizable digital signage solution, leveraging an outdoor rated high brightness 55" LCD display and a robust content management system (CMS). The LCD-NAV system can be used at facility or level entrance locations to display occupancy data, general wayfinding, or promotional information. \*Media player required, sold separately.

The cloud hosted CMS allows the LCD-NAV system to be configured and monitored remotely.





Part Numbers:

LCD-NAV 55 SV: 55" 1080p high brightness outdoor LCD display, 2500 nit, auto-brightness, IP66, IK10, extended temperature, silver

LCD-NAV 55 BK: 55" 1080p high brightness outdoor LCD display, 2500 nit, auto-brightness, IP66, IK10, extended temperature, black

<b>Content Display</b>	
Capabilities	Static text or dynamic digits, HD graphics, weather, date/time, photo library and similar widgets
Display	55 LED-backlit LCD screen, commercial grade
Resolution	1920 x 1080 (HD)
Brightness	2500 cd/m, automatic brightness with ambient light sensor
Maximum Viewing Angle	178° x 178°

<b>Environment</b>	
Ingress Protection	Display: IP66 Media Cabinet: IP55
Media Cabinet Ventilation	Louvered vents with fans
Operating Temperature	-35° to 60°C (-31° to 140°F)
Wind Rating	Wind tested up to 215 km/h (135 mph)

<b>Electrical</b>	
Power	110V AC 60 Hz, 4A
Power Draw	200 W (typical)
Product Safety	UL Listed

<b>Construction</b>	
Housing	Stainless steel and aluminum, smooth powder coat
Mounting	Attached to floor
Service Access	Media player cabinet accessed from front Display connections accessed from rear

<b>Dimensions</b>	
Height	2137 mm (84.1)
Width (housing)	898 mm (35.4)
Depth (housing)	252 mm (10)
Weight	128 kg (283 lbs)







## RELATED



**TKH Security VMS-NAV 1x2 Aisle Sign**  
VMS-NAV 1x2



**TKH Security M5 Sensor**  
Camera Sensor, 5th Generation, single camera, daisy chain



**TKH Security M5 Power Cabinet**  
Cabinet for M5 ecosystem