

LCD-VMS NAV

VMS-NAV 1x2

DESCRIPTION

The Park Assist LCD-NAV 55 is a highly customizable digital signage solution, leveraging an outdoor rated high brightness 55" LCD display and a robust content management system (CMS). The LCD-NAV system can be used at facility or level entrance locations to display occupancy data, general wayfinding, or promotional information. *Media player required, sold separately.

The cloud hosted CMS allows the LCD-NAV system to be configured and monitored remotely.





Part Numbers:

LCD-NAV 55 SV: 55" 1080p high brightness outdoor LCD display, 2500 nit, auto-brightness, IP66, IK10, extended temperature, silver

LCD-NAV 55 BK: 55" 1080p high brightness outdoor LCD display, 2500 nit, auto-brightness, IP66, IK10, extended temperature, black

Content Display	
Capabilities	Static text or dynamic digits, HD graphics, weather, date/time, photo library and similar widgets
Display	55 LED-backlit LCD screen, commercial grade
Resolution	1920 x 1080 (HD)
Brightness	2500 cd/m, automatic brightness with ambient light sensor
Maximum Viewing Angle	178° x 178°

Environment	
Ingress Protection	Display: IP66 Media Cabinet: IP55
Media Cabinet Ventilation	Louvered vents with fans
Operating Temperature	-35° to 60°C (-31° to 140°F)
Wind Rating	Wind tested up to 215 km/h (135 mph)

Electrical	
Power	110V AC 60 Hz, 4A
Power Draw	200 W (typical)
Product Safety	UL Listed

Construction	
Housing	Stainless steel and aluminum, smooth powder coat
Mounting	Attached to floor
Service Access	Media player cabinet accessed from front Display connections accessed from rear

Dimensions	
Height	2137 mm (84.1)
Width (housing)	898 mm (35.4)
Depth (housing)	252 mm (10)
Weight	128 kg (283 lbs)





RELATED



TKH Security VMS-NAV 1x2 Aisle Sign
VMS-NAV 1x2



TKH Security M5 Sensor
Camera Sensor, 5th Generation, single camera, daisy chain



TKH Security M5 Power Cabinet
Cabinet for M5 ecosystem