

NEOVO-X-19E

Monitor 19", LED, Full HD, SXGA, 24/7, VGA, DVI, HDMI, DP

DESCRIPTION

Much more than a desktop monitor, the X-19E is a high-resolution 19" display with NeoV™ Optical Glass that protects the display from scratches, accidents, and incidental damage. With strong metal casing design and the flexibility of analogue, DVI, S-Video and CVBS video inputs, the X-19E provides the versatility that is essential in multi-user environments.

FEATURES

High 1280 x 1024 SXGA resolution

Support Full HD 1920 x 1080

NeoV Optical Glass and durable metal housing

Supports PIP and PBP functions; 3D De-interlace/Noise Reduction

Swift 3 ms response time

Versatile connectivity: VGA, DVI, HDMI, DisplayPort, Audio in

Built-in speakers (2 W x 2)

EcoSmart Sensor for low watt power consumption

Touch sensor control keys to prevent vandalism

Auto-adjustment for optimal settings

Durable metal casing

VESA standard wall mount



Panel

Panel Type	LED-backlit TFT LCD
Panel Size	19.0 (482 mm)
Max. Resolution	SXGA 1280 x 1024
Pixel Pitch	0.294 mm
Brightness	250 cd/m2 (Typical)
Contrast Ratio	1000:1 (Typical)
Viewing Angle (H/V)	170°/160° (Typical)
Display Colour	16.7M
Response Time	3 ms (GTG)

Frequency

Frequency (H/V)	H: 15 kHz - 81 kHz V: 50 Hz - 85 Hz
-----------------	--

Input

VGA	15-Pin D-Sub
DVI	24-Pin DVI-D
HDMI	HDMI 1.4
DisplayPort	DisplayPort 1.2a

Audio

Audio In	Stereo audio jack for PC (3.5 mm) x 1
Speaker	2W x 2

Power

Power Supply	External
Power Requirements	DC 12V
Consumption	21 W (On) < 0.5 W (Stand-by)

NeoV Optical Glass

Thickness	3.0 mm (0.12)
Reflection Rate	< 1%
Transmission Rate	> 96%
Coating Hardness	> 9H

Plug & Play

VESA	DCC 2B, DCC/CI
------	----------------

Operating Conditions

Temperature	0 °C ~ 40 °C
Humidity	10% ~ 90%

Storage Conditions

Specs



Storage Conditions

Temperature	-20 °C ~ 60 °C
Humidity	5% ~ 95%

Mounting

VESA FPM PMI	Yes (100 x 100mm & 75 x 75mm)
--------------	-------------------------------

Ergonomics

Tilt	0 ° ~ 20 °
------	------------

Dimensions

Product (W x H x D)	445.4 x 420.2 x 175mm (17.5 x 16.5 x 6.9)
Packaging (W x H x D)	552 x 526 x 225mm (21.7 x 20.7 x 8.9)

Weight

Product w/o base	6kg (13.2lbs)
Product w base	6.8kg (15.0lbs)
Packaged	8.4kg (18.7lbs)

Regulation Approval

Certifications & Compliance	CB, CE, WEEE, EuP/Erp, REACH
-----------------------------	------------------------------

Supplied accessories

Accessories	Power Cord, Power Adaptor, VGA cable, DVI to HDMI cable, Quick Start Guide, Audio Cable, Warranty
-------------	---

Ordering Info

NEOVO-X-19E	Monitor 19", LED, Full HD, SXGA, 24/7, VGA, DVI, HDMI, DP
-------------	---

Display accessories

FPMA-W25	Fixed wall mount for 10-30" flat panel displays
FPMA-W75	Fixed wall mount for 10-30" flat panel displays
FPMA-W830BLACK	4 Movements wall mount for 10-30" flat panel displays
FPMA-C050BLACK	Ceiling mount for 10-30" flat panel displays, 50-85cm
FPMA-C100	Ceiling mount for 10-26" flat panel displays, 79-129cm







RELATED



AGNeovo Neovo-X-22E

Monitor 22", LED, Full HD, DVI/VGA/HDMI/Displayport, 24/7



AGNeovo Neovo-X-24E

Monitor 24", LED, Full HD, DVI/VGA/HDMI/DisplayPort, 24/7
