



NVH-1504XR.C

Video server 19", 4U, 5 bay HS, Xeon, SSD, RAID

DESCRIPTION

The NVH-1504XR.C series is a powerful, stackable and rack-mounted VDG Sense server build for the ObjectC algorithm. It combines top quality components and a user-friendly configuration deliver high-power output and reliability. It's casing and components are engineered to ensure an optimized airflow (even when stacked) for higher efficiency.

FEATURES

4U Compact Server Chassis

Specially built for object classification

5x 3.5" hot swappableHDD bays

Standard RAID 5configuration

Supports PS/2 single and 1+1 redundant PSU

Dual Ethernet (1gb/s) ports

Front-side USB ports for easy access (2x USB 2.0)

Slide rail included

Powerful NVIDIA video card for classification





The front-mounted hard-drives are configured for hot-swapping, as are the cooling fans, to ensure 24/7 operation. This means that they are easy to service and can reduce running costs. The reliability is ensured through a standard RAID 5 configuration and redundancy, but can be configured otherwise if necessary..

Optional expansions:

• VDG Video server storage



System									
Operating system	Windows 11 IoT En	terprise LTSC 202	24						
Hard disk OS	NVMe 512GB SSD	(included)							
Raid configuration	Standard Raid 5 co	nfiguration (RAID	config option	s:0,1,5,6	, 10 and hot	-spare)			
Processor	Intel Xeon E2300 p	rocessor							
Chipset	Intel C256 Chipset	Intel C256 Chipset							
Memory	16GB memory DDF	₹4							
Network Interface	2 x 1GbE LAN + 1 :	x Mgmt LAN							
	LAN controller supp	LAN controller supports 100Base-T, 1000Base-T							
TPM	TPM 2.0	TPM 2.0							
Management	Remote manageme	ent module includ	ed						
RAID controller	12Gb/s SAS and SA	ATA RAID controll	er						
Video output	VGA (HDMI output	VGA (HDMI output not supported)							
Drive bay	5 x 3.5" Hot-swap	5 x 3.5" Hot-swap							
Mechanical									
Form Factor	4U 19-inch Rack Mo	4U 19-inch Rack Mount							
Dimensions (DxWxH)	562 mm x 430 mm	562 mm x 430 mm x 176 mm (22.1 x 16.9 x 6.9)							
Electrical									
	400 040 44 0 50 44								
Power Input	<u> </u>	100-240VAC,50/60Hz 5A							
Power Supply		650W Single (standard)							
	•	500W Redundant power supply (upgrade)							
Power consumption		Idle: 80 100 Watt Max Power: 250 Watt (Tested with 32 to 64 channels of objectC)							
	Max Power : 250 vv	att (Tested with 3	2 to 64 chanr	ieis of objec	TC)				
Ordering Info									
Description	NVH-1504XRC - Cr	NVH-1504XRC - Crowd Manag. server 19", 4U, 4 bay HS, Xeon, SSD, RAID, RTX							
Environmental									
Operating Temperature	5° C - 40° C (41°F -	5° C - 40° C (41°F - 104°F)							
Storage Temperature		-40° C - 65° C (-40°F - 149°F)							
Supplied Accessories		USB Compact Keyboard							
		USB Optical Mouse							
	<u>'</u>	Power Cord 1.5 meter							
	Slide rail	Slide rail							
Basic video server storage	NVH-81TB NVH-8	2TB NVH-83TR	NVH-84TR	NVH-84TR	NVH-88TR	NVH-810T			
(incl. assembly and config)	1TB 2TB	3TB		6TB	8TB	10TB			
Pro video server storage	NVH-92TB	NVH-94TB	NVH-9	76ТВ	NVH-98	ТВ			
(incl. assembly and config)	2TB	4TB	6TB		8TB				
	NVH-910TB NVH-912TB NVH-914TB NVH-916TB NVH-918TB								

Specs



10TB	12TB	14TB	16TB	18TB















RELATED



Toshiba NVH Pro Server Storage

Professional server storage for the most demanding storage environments.