

# NVH-1504XR

Video server 19", 4U, 5 bay HS, Xeon, SSD, RAID, RPSU

## DESCRIPTION

The NVH-1504XR is a powerful, 4U, rack-mounted VDG Sense server. The hard- and software of the NVH-1504XR is selected for a standalone VDG Sense Server. The hardware consist only of top-quality components from third party manufacturers as Asus, Western Digital and Intel.

### FEATURES

4U Compact Server Chassis

Standalone server

5x 3.5" hot swappableHDD bays

Standard RAID 5configuration

OS RAID 1 configuration (optional)

Supports PS/2 single and1+1 redundant PSU (optional)

Dual Ethernet (1gb/s) ports

Front-side USB ports for easy access (2x USB 2.0)

Slide rail included





The front-mounted hard-drives are configured for hot-swapping, as are the cooling fans, to ensure 24/7 operation. This means that they are easy to service and can reduce running costs. The reliability is ensured through a standard RAID 1 configuration for OS redundancy, and RAID 5 configuration for data redundancy, but can be configured otherwise if necessary. Redundant power supply included.

Optional expansions:

- VDG Video server storage
- NVH-GBLAN for 1 extra Ethernet connection port
- Ethernet server adapter fiber



Pro video server storage	NVH-92TB NVH-94TB NVH-96TB NVH-98TB					
(incl. assembly and config)	1TB 2TB 3TB 4TB 6TB 8TB 10TB					
Basic video server storage	NVH-81TB NVH-82TB NVH-83TB NVH-84TB NVH-86TB NVH-88TB NVH-81					
NVH-RPSU-500W	Redundant PSU for NVH-1504IR (to replace standard NVH-1504IR PSU)					
NVH-I350F2	Ethernet server adapter fiber					
NVH-GBLAN	Extra 100/1000Mbps LAN interface					
NVH-QUAD	Quad mini displayport/DVI-D output					
VDG Server accessories						
	Slide rail					
	USB Optical Mouse Power Cord 1.5 meter					
Supplied Accessories	USB Compact Keyboard					
NVH-1504XR	Video server 19", 4U, 4 bay HS, i7, SSD, RAID					
Storage Temperature	-40° C - 65° C (-40°F - 149°F)					
Operating Temperature	5° C - 40° C (41°F - 104°F)					
Environmental						
Power Consumption	250W					
	500W Redundant power supply (upgrade)					
Power Supply	650W Single (standard)					
Power Input	100-240VAC,50/60Hz 5A					
Electrical						
Dimensions (DxWxH)	562 mm x 430 mm x 176 mm (22.1 x 16.9 x 6.9)					
Form Factor	4U 19-inch Rack Mount					
Mechanical						
Drive bay	5 x 3.5" Hot swap					
Video output	VGA (HDMI output not supported)					
RAID controller	12Gb/s SAS and SATA RAID controller					
Management	Remote management module included					
ТРМ	TPM 2.0					
	LAN controller supports 100Base-T, 1000Base-T					
Network Interface	2 x 1GbE LAN + 1 x Mgmt LAN					
Memory	16GB memory DDR4					
Chipset	Intel C256 Chipset					
Processor	Intel Xeon E2300 processor					
Raid configuration	Standard Raid 5 configuration (RAID config options : 0, 1, 5, 6, 10 and hot-spare)					
Hard disk OS	NVMe 512GB SSD (included)					
Operating system	Windows 11 IoT Enterprise LTSC 2024					

# Specs



Pro video server storage					
(incl. assembly and config)	2TB	4TB		6TB	8TB
	NVH-910TB	NVH-912TB	NVH-914TB	NVH-916TB	NVH-918TB
	10TB	12TB	14TB	16TB	18TB











# RELATED



#### Intel NVH-GBLAN

A PCI Express Ethernet adapter perfect for expanding your Ethernet port(s).



### Toshiba NVH Pro Server Storage

Professional server storage for the most demanding storage environments.