

NVH-2516XR (EOL)

Video server 19", 3U,16 bay HS, Xeon, SSD, RAID, RPSU

DESCRIPTION

The NVH-2500 series are powerful, customizable, stackable and rack-mounted VDG servers. It combines top quality components and a user-friendly configuration to deliver high-power output and reliability. It's casing and components are engineered to ensure an optimized airflow (even when stacked) for higher efficiency, which results in lower energy consumption. Its redundant hot-plug power supply ensures a continuous operation at all times.

FEATURES

3U Rack-mountable Server Chassis

16x 3.5" hot swappableHDD bays

Standard RAID 5configuration

650W Reduntant Hot-plug Power Supply

16-Port 12G Mini-SAS Expander Backplane

Two Ethernet (1gb/s) ports

One Active Management Technology (AMT) port

Front access info tag for easy server management

Slide rail



Built as stand-alone servers, the NVH-2500 series; front-mounted hard-drives are configured for hot-swapping, as are the cooling fans, to ensure 24/7 operation. This means that they are easy to service and can reduce running costs.

The reliability is ensured through a standard RAID 5 configuration and redundancy, but can be configured otherwise if necessary. Optionally, a hot-standby hard-drive can be configured to ensure maximum reliability and reduce service needs. The NVH-2516XR contains 16 slots for hard-drive storage.

Optional expansions:

- VDG Video server storage
- NVH-GBLAN for 1 extra Ethernet connection port
- Ethernet server adapter fiber
- 1x NVH-RMM for remote management access

System	
Operating system	Microsoft Windows 10 Pro 64-bit
Hard disk	128GB SSD (included)
Recording storage capacity	Up to 288TB (16 x 3.5" hard disk drives)
Raid configuration	Standard Raid 5 configuration
Effective recording storage capacity	270TB (after Raid 5)
Processor	Intel Xeon E3 processor
Chipset	Intel C232 Chipset
Memory	16GB memory
Network Interface	Dual Gigabit Ethernet RJ-45 (10/100/1000 MB/s)
Video output	VGA

Mechanical	
Form Factor	U 19-inch Rack Mount
Dimensions (DxWxH)	660mm x 429mm x 132mm (26" x 16.9" x 5.2")

Electrical	
Power Input	100-240VAC, 50/60Hz 5A
Power Supply	650W Redundant hot-plug

Environmental	
Operating Temperature	5° C - 40° C (41°F - 104°F)
Storage Temperature	-40° C - 65° C (-40°F - 149°F)

Ordering Info	
NVH-2516XR	Video server 19", 3U, 16 bay HS, Xeon, SSD, RAID, RPSU
Supplied Accessories	USB Compact Keyboard
	USB Optical Mouse
	Power Cord 1.5 meter
	Slide rail

VDG Server accessories	
NVH-GBLAN	Extra 100/1000Mbps LAN interface
NVH-FIBER	Ethernet server adapter fiber

Basic video server storage	NVH-84TB	NVH-86TB	NVH-88TB	NVH-810TB	
(incl. assembly and config)	4TB	6TB	8TB	10TB	
Pro video server storage	NVH-92TB	NVH-94TB	NVH-96TB	NVH-98TB	
(incl. assembly and config)	2TB	4TB	6TB	8TB	
	NVH-910TB	NVH-912TB	NVH-914TB	NVH-918TB	NVH-918TB
	10TB	12TB	14TB	16TB	18TB







RELATED



Intel NVH-GBLAN

A PCI Express Ethernet adapter perfect for expanding your Ethernet port(s).



VDG

Video server 19", 3U,16 bay HS, Xeon, SSD, RAID, RPSU



Toshiba NVH Pro Server Storage

Professional server storage for the most demanding storage environments.