

# NVH-2624XR

Video server 19", 4U, 24 bay HS, Xeon, SSD, RAID, RPSU

## DESCRIPTION

The NVH-2000 series are powerful, customizable, stackable and rack-mounted VDG servers. It combines top quality components and a user-friendly configuration to deliver high-power output and reliability. It's casing and components are engineered to ensure an optimized airflow (even when stacked) for higher efficiency, which results in lower energy consumption. Its redundant hot-plug power supply ensures a continuous operation at all times.

## FEATURES

---

4U Rack-mountable Server Chassis

---

24x 3.5" hot swappableHDD bays

---

Standard RAID 5configuration

---

875W Reduntant Hot-plug Power Supply

---

1x 24-Port 12G Mini-SAS HD Expander Backplane

---

Dual Intel I210AT Gigabit Ethernet with teaming support

---

Front access info tag for easy server management

---

Slide rail included



Built as stand-alone servers, the NVH-2500 series front-mounted hard-drives are configured for hot-swapping, as are the cooling fans, to ensure 24/7 operation. This means that they are easy to service and can reduce running costs.

The reliability is ensured through a standard RAID 5 configuration and redundancy, but can be configured otherwise if necessary. Optionally, a hot-standby hard-drive can be configured to ensure maximum reliability and reduce service needs. The NVH-2524XR contains 24 slots for hard-disk storage.

**Optional expansions:**

- VDG Video server storage
- NVH-GBLAN for 1 extra Ethernet connection port
- Ethernet server adapter fiber

<b>System (Rev O6-2026)</b>	
Operating system	Windows 11 IoT Enterprise LTSC 2024
Hard disk OS	NVMe 1Tb SSD
Processor	Intel Xeon E processor
Chipset	Intel C266 Chipset
Memory	16GB memory DDR5
Network Interface	2 x 1 GbE LAN + 1 x Mgmt LAN
	On-Board ASMB11-iKVM for KVM-over-IP
TPM	TPM 2.0
Management	Remote management module included
RAID controller	12Gb/s SAS and SATA RAID controller
Raid configuration	Standard Raid 5 configuration (RAID config options : 0, 1, 5, 6, 10 and hot-spare)
Video output	VGA
Drive bay	24 x 3.5" Hot swap

<b>Mechanical</b>	
Form Factor	19-inch Rack Mount
Dimensions (DxWxH)	698mm x 432mm x 176mm (27.5" x 17" x 6.9")

<b>Electrical</b>	
Power Input	100-240VAC,50/60Hz,10-8A
Power Supply	1200W Redundant Hot-plug

### **Environmental**

<b>Environmental</b>	
Operating Temperature	10°C to 50°C (50°F to 122°F)
Non-operating (Storage) Temperature	-40°C to 70°C (-40°F to 158°F)
Non-operating (Storage) Relative Humidity	20% to 90% (non-condensing)

### **Ordering Info**

NVH-2624XR	Video server 19", 4U, 24 bay HS, Xeon, SSD, RAID, RPSU
Supplied Accessories	USB Compact Keyboard
	USB Optical Mouse
	Power Cord 1.5 meter
	Slide rail

### **VDG Server accessories**

NVH-GBLAN	Extra 100/1000Mbps LAN interface
NVH-FIBER	Ethernet server adapter fiber

<b>Pro video server storage</b>	<b>NVH-92TB</b>	<b>NVH-94TB</b>	<b>NVH-96TB</b>	<b>NVH-98TB</b>
(incl. assembly and config)	2TB	4TB	6TB	8TB

	<b>NVH-910TB</b>	<b>NVH-912TB</b>	<b>NVH-914TB</b>	<b>NVH-916TB</b>	<b>NVH-918TB</b>
--	------------------	------------------	------------------	------------------	------------------

# Specs



---

10TB	12TB	14TB	16TB	18TB
------	------	------	------	------

---







## RELATED

---



### **Intel NVH-GBLAN**

A PCI Express Ethernet adapter perfect for expanding your Ethernet port(s).

---



### **Toshiba NVH Pro Server Storage**

Professional server storage for the most demanding storage environments.

---