



# TL3-UN-B

### **TANLock Rack handle - RFID**

#### DESCRIPTION

iProtect not only offers a modern and flexible Access Management System to secure buildings and other locations, but also offers an efficient way to protect your knowledge, processes and data through a central and tamper-proof locking system, the "TANLock Rack handle".

TANLock Rack handle may be used for all areas which need to be secured such as, data centers, control cabinets on production plants or in your critical infrastructure. With implementing this system, you ensure that only authorized persons have access to your business-critical areas. Furthermore, you can monitor the status of each individual cabinet door online. TANLock Rack handle, is available in the colors black and silver.

#### **FEATURES**

Suitable for all universal Racks

RFID Technology: Mifare DESfire / UID

OK button to confirm remote opening

Can be powered-up incase of emergency via USB-C





Power supply & consumption	
Voltage	PoE : IEE 802.3af-2003
Power consumption	min. 4.8W
Measure	
Measurements Housing	239,0 x 40,0 x 28,0 mm
Weight	680g
Environment	
Rating	IPXX Optional IP54 IP65
Operating temp	-40 65C
Operating humid	5 95% relative humidity, non-condensing
Storage temp	-40 85C
Inputs	
Digital input IN0	Door status
Digital input IN1	Side panel status
USB-C	External power via USB-C connector
035 C	External power via 652 6 connector
Cardreader	
Standard	ISO 14443-A
Frequencies	13,56MHz
Туре	Mifare DESFire and UID
Reading Distance	0-30mm (normal operation)
Indicators	
ORANGE LED	Handle rotation status
BLUE LED	Access status
RED LED	Alarm status
Certification	
Certification	ElectricEMC / CE
Variants	
TL3-UN-B	TANlock RFID
TL3-UN-PIN-B	TANlock RFID, PIN
TL3-UN-MO-B	TANlock RFID, MO
TL3-UN-PIN-MO-B	TANlock RFID, PIN MO
TL3-UN-S	TANlock Rittal silver
TL3-UN-PIN-S	TANlock PIN Rittal silver
TL3-UN-MO-S	TANlock MO Rittal silver
TL3-UN-PIN-MO-S	TANlock PIN MO Rittal silver
	TANlock Vertiv
	TANlock PIN Vertiv

## Specs



Variants	
	TANlock MO Vertiv
	TANlock PIN MO Vertiv
Colours	
xxx-xxxx-S	Black
xxx-xxxx-B	Silver
Mechanical Override	
Cylinder size	
Door contacts	
512-2013	TANlock Door contact 2m
512-2014	TANlock Door contact 3m
512-2015	TANlock Door contact 0.08m



























#### RELATED

