

VPSU243EXT

External power supply unit

DESCRIPTION

The VPSU243EXT has been designed to provide installers with a complete range of options to cover any likely requirement. The PSU243EXT is housed in a robust IP68 rated casing, feature easy to change fuses, and 2 fitted glands for the safe routing of Power IN and OUT cables.

FEATURES

IP68 rated external enclosure

Cable glands

Safe fuse removal



Input

Voltage	230VAC Nominal (+10% / -15%)
Frequency	50Hz
Fuse (F5)	T2A - 20mm 230v HRC

Output

Nominal Voltage	24VAC (@230VAC input)
Voltage Range	23VAC to 28VAC (On full load to off load @230VAC)
Fuse	F3.15A - 20mm Glass type - 230V

Physical

Environment	-100C to 400C @ up to 95% RH, IP68 external enclosure
Dimensions	200H x 150W x 100D (mm)
Mounting holes	182.5 x 131 (mm)
Weight	Approx 1.5Kg
Connections	Mains input: Live (Brown), Neutral (Blue)
Compliance	Low Voltage: 2014/35EU, EMC: 2104/30/EU, RoHS2: 2011/65/EU, WEEE: 2012/19/EU

Ordering info

VPSU243EXT	External PSU, 24VAC, 3A, in housing
------------	-------------------------------------