



FATH Mechatronics GmbH Gewerbepark Hügelmühle 31

91174 Spalt Deutschland

Tel:+49 9175 7909-152 Fax: +49 9175 7909-119

info@tanlock.com www.tanlock.com

facebook.com/fath.mechatronics twitter.com/f mechatronics instagram.com/fathmechatronics



TANlock 3



ELECTRIC INTEGRATED

The MODULAR **SCALABLE**

SECURE



Access Control System









www.tanlock.com

ELECTRIC INTEGRATED Access Control System The MODULAR SCALABLE SECURE



CHOOSE YOUR MODULE:









PIN + RFID



Hand Vein Scan







Fingerprint Scan



Touch Display



YOUR TANlock 3

TANlock 3

Through individual authentication modules (TAM), TANlock 3 can be adjusted to nearly every customer requirement. The TAMs (TANlock Authentication Modules) can be replaced and changed to whatever authentication method is needed, even after years.

Through the many standard interfaces, you can easily set up the TAN*lock* 3 to your IT infrastructure. In a consistent way there is no administrative software needed.

Additional Features:

• PoE: Power over Ethernet • HTTPS • Syslog • MS Active Directory • LDAPs • RESTful API • Web API • SNMP

Remote

▶ Remote access

• External sensors like temperature, humidity over CAN-Bus



Hand Vein Scan

→ Highest security level through hand vein detection via PalmSecure



PIN + RFID

- **→** Two-factor authentication
- → Authentication via PIN or RFID(13,56 MHz)
- → Legic Advant, HID iCLASS, Mifare Desfire EV1, EV2
- → BTLE (Bluetooth Low Energy)



Fingerprint Scan

→ Biometric procedure protects from abuse



Touch Display

- → Authentication through entry at the touch display
- → Displays operation parameters like temperature, humidity, ...



